

AIP-W525H

802.11b/g/n Long-Range 2T2R AP/Router



AIP-W525H is the long-range 4LAN + 1WAN AP/Router, support more than 2x coverage range than other router, also provide high-speed data-rate up to 300Mbps.

FEATURES

- 2.4GHz IEEE 802.11n 2x2 MIMO
- Complies with IEEE 802.11bg
- Data-rate up to 300Mbps
- High power and High sensitivity
- Wide coverage
- RF output power adjustable
- Firewall, URL/IP/Port/MAC filtering
- Firmware upgrade via HTTP
- Support Gateway, Bridge and WISP mode
- Multiple ESSID
- Telnet Supported
- QoS enhancement-WMM
- Selected Country Code
- WAN remote port configuration
- TCP/UDP/ICMP/ARP protocol stack
- Virtual DMZ, Port forwarding
- Easy setup wizard
- Web-based utility
- Passive PoE

For further details:
Alfa Network Inc.,
4F-1 No. 106, Rueiguang Rd.,
Neihu District,
Taipei City, Taiwan.
<http://www.alfa.com.tw>
sales@alfa.com.tw

AIP-W525H

802.11b/g/n Long-Range 2T2R AP/Router

SPECIFICATION

Model		AIP-W525H	
Standard	IEEE 802.11b/g/n	Operation Mode	Gateway Bridge Wireless ISP
Chipset	RTL8196C		
Flash/SDRAM	2M / 16M		
Antenna	2x 5dBi antennas detachable	Wireless Mode	AP Client WDS AP+WDS
Frequency	2.400~2.483GHz	Data Rate	802.11b: 11, 5.5, 2, 1Mbps 802.11g: 54, 48, 36, 24, 18, 12, 9 & 6Mbps 802.11n(20MHz): up to 144Mbps 802.11n(40MHz): up to 300Mbps
Output Power	802.11b: up to 28 ± 1 dBm 802.11g: up to 26 ± 1 dBm 802.11n: up to 26 ± 1 dBm		
Sensitivity	-96dBm @ 802.11b -91dBm @ 802.11g -91dBm @ 802.11n		
Security	64/128bit WEP WPA(TKIP with IEEE 802.1x) WPA2(AES with IEEE 802.1x) WPA Mixed 802.1x authentication		
Operation Temperature	-20°C ~ 60°C	Power requirement	DC Jack: 12V DC PoE: 12V Passive PoE
Dimension(mm)	147 x 98 x 30 mm	Storage Humidity	10% ~ 90% (Non-condensing)
		Interface	RP-SMA antennas connector x 2 RJ-45 WAN port x 1 RJ-45 LAN ports x 4

